

**DECLARATION OF PERFORMANCE****No. 189-04-CPR-2018-03-19**

1. Unique identification code of the product-type:

**Product plastomeric
modified reinforced bitumen sheet Scutumplast APP EMP 3.8R**

Size	Protective coating	Product number
5x1	Sand-film	TN569859

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Designed for installation as one-layer of roof cladding on buildings and constructions and for waterproofing of engineering structures. Used for new roofing construction and for repair of old roof. Applied as single-layer roofs and at placing by a cold method - by means of mechanical fixings; fastened to the basis by means of fixtures that are installed at overlappings. Traditional placing by melting and partial melting is possible also.

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**TechnoNicol-Vyborg Ltd.,
Ruberoïdnaya St., 7, Leningradskaya region, Vyborg, 188804, RUSSIA
Tel. +78137839072
Fax. +78137839091
Email: Main@vbg.tn.ru**

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**TechnoNicol-Construction systems LLC,
Gilyarovskogo St., 47/5, Moscow 129110, RUSSIA
Tel. +74959255575
Fax. +74959805249
Email: europe@tn.ru
Website: www.tn-europe.com**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

6. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

6a. **EN 13707:2004+A2:2009**

6b. **Notified certification body No. 1023 - INSTITUTE FOR TESTING AND CERTIFICATION, Plc.
performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control.**

This certificate 1023-CPR-0546 F, was first issued on December 17. 2014



7. Declared performance

Scutumplast APP EMP 3.8R

No		The indicator name	Test method	Unit of measure	Norm
Polyester fiber reinforced					
1		Protection of the top side			See item number 1
2		Protection of the bottom side			
3	MLV	Rolls length,	EN 1848-1	mm	
4	MLV	Rolls width	EN 1848-1	mm	
5	Pass	Straightness	EN 1848-1	mm	≤ 1 mm to 1 meter
6	MDV	Mass per unit area	EN 1849-1	kg/m ²	5,0 ± 0.25
7	MDV	Thickness	EN 1849-1	mm	3.8 ± 0.2
8		Visible defects	EN 1850-1	-	Visible defects
9	MLV	Cold flexibility, °C / Ø 30 mm- upper face and lower face	EN 1109-1	°C	≤ -15
10	MLV	Flow resistance at elevated temperature, °C / 2 h - upper face and lower face	EN 1110	°C	≥ 140
11	MDV	Elongation, L/T	EN 12311-1	%	50/50 ± 15%
12	MDV	Tensile strength, L/T	EN 12311-1	N/50mm	800/600 ± 20%
13	MLV	Dimensional stability, +80 °C/24 h, L. method B	EN 1107-1	%	≤ ± 0.3
14	MDV	Nail shank tear resistance, L/T	EN 12310-1	N	150/150 -0/+250
15	Pass	Watertightness (method B)	EN 1928	kPa	300
16	MLV	Resistance to impact at +23 °C/Ø12.7 mm (500 g/h.mm). method B	EN 12691	mm	h≥1000
17	MLV	Resistance to impact at +23 °C/Ø12.7 mm (500 g/h.mm). method A	EN 12691	mm	h≥600
18	MLV	Resistance to static loading, 200 N (20 kg) Method A (EPS support)	EN 12730	kg	15
19		Reaction to fire	EN 13501-1:2004		EUROCLASSE F
20		External fire exposure*	EN 13501-5		F roof B roof t1*
21		Determination of water vapor transmission properties	EN 1931	—	μ=20000
Properties after artificial ageing/ EN 1296/. 12 weeks at +70 °C					
22	MDV	Flow resistance at elevated temperature, °C/2 h - upper face and lower face	EN 1110	°C	≥ 130
23	MDV	Cold flexibility, °C/Ø 30 mm- upper face and lower face	EN 1109-1	°C	-5

*in system: steel deck 0.75 mm, profile 106/Eps insulation, quality EPS100, thickness 100 mm, Euroclass E/
separation layer of plain glass fleece, 100 g/m²

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: [name]... Deputy Quality Director

At [place]... TechnoNicol-Vyborg, Ltd.....on [date of issue]...2018.03.19.....

[Signature].....Galina Grablina.....

